

# INSTALLATION GUIDE



## TCP COLVF-12 Polished Stainless Tower Adapter Cap



### PARTS LIST

Qty	Part Number	Description
2	7909-055	Cap, Tower Adapter, Polished Stainless Steel
2	3105-025-F0.50-H	Flat Head, 1/4-28 x 1/2" Cap Screw, Polished Stainless

### INSTRUCTIONS

1. After you have completed the installation of the Bolt-In Coil-Over or ShockWave™ suspension conversion, thread the zerk fitting into the shock pivot stud and grease it with a grease gun.
2. Once it is greased, remove the zerk fitting.
3. Place the tower adapter cap over the shock pivot stud and secure with the 1/4-28 x 1/2" flat head cap screw.
4. When you need to grease the pivot stud remove the cap and thread in the zerk fitting.

#### WARRANTY NOTICE:

There are NO WARRANTIES, either expressed or implied. Neither the seller nor manufacturer will be liable for any loss, damage or injury, direct or indirect, arising from the use or inability to determine the appropriate use of any products. Before any attempt at installation, all drawings and/or instruction sheets should be completely reviewed to determine the suitability of the product for its intended use. In this connection, the user assumes all responsibility and risk. We reserve the right to change specification without notice. Further, Chris Alston's Chassisworks, Inc., makes **NO GUARANTEE** in reference to any specific class legality of any component. **ALL PRODUCTS ARE INTENDED FOR RACING AND OFF-ROAD USE AND MAY NOT BE LEGALLY USED ON THE HIGHWAY.** The products offered for sale are true race-car components and, in all cases, require some fabrication skill. **NO PRODUCT OR SERVICE IS DESIGNED OR INTENDED TO PREVENT INJURY OR DEATH.**

Total Control Products  
A Chris Alston's Chassisworks, Inc. Brand  
8661 Younger Creek Drive  
Sacramento, CA 95828  
Phone: 916-388-0288  
Technical Support: [tcptech@cachassisworks.com](mailto:tcptech@cachassisworks.com)

