READ ALL INSTRUCTIONS COMPLETELY AND THOROUGHLY UNDERSTAND THEM BEFORE DOING ANYTHING. CALL CHASSISWORKS TECH SUPPORT (916) 388-0288 IF YOU NEED ASSISTANCE.

INSTALLATION GUIDE



5908-RB-HP

Remote Breather Vent and Hose Kit



Description:

Billet-Aluminum Vent provides components to add a -8 AN size, 40-micron sintered bronze vent to a fuel tank, rear axle housing or transmission, without routing through a reservoir canister. For fuel tanks, axle housings and transmissions.

WARNINGS

- To minimize the risk of fire, avoid routing hoses or mounting vent in areas of high heat, or that may have the possibility of an ignition spark.
- Hoses must be routed clear of any moving vehicle components and securely mounted to avoid damage from abrasion or fatigue.
- Check valves are required on hoses to prevent fluid flow into the vent hose on performance applications, such as road racing, or in the event of vehicle rollover.
- Do not use with nitromethane fuel.
- Vent must be mounted outside of the trunk, so that it vents to open air.
- Hoses must only run downhill from the vent, avoiding any uphill bends along the hose length for fluid or condensation to drain properly.

Part Number	Image	Description
5908-RB-HP		Remote Breather Vent and Hose Kit provides components to add a -8 AN size, 40-micron sintered bronze vent to a fuel tank, rear axle housing or transmission, without routing through a reservoir canister. Contains 36" length -6 black push-lite race hose, two hose clamps, one straight -6 push-lock hose end, one 45-degree -6 push-lock hose end, one 90-degree -6 push-lock hose end, -8 sintered bronze vent, -8 to -6 bulkhead adapter with jam nut, mounting bracket and hardware. (Chassisworks hose kits provide 3 different Hose ends to allow the best line routing even though only 2 are required)

WARRANTY NOTICE:

There are NO WARRANTIES, either expressed or implied. Neither the seller nor manufacturer will be liable for any loss, damage or injury, direct or indirect, arising from the use or inability to determine the appropriate use of any products. Before any attempt at installation, all drawings and/or instruction sheets should be completely reviewed to determine the suitability of the product for its intended use. In this connection, the user assumes all responsibility and risk. We reserve the right to change specification without notice. Further, Chris Alston's Chassisworks, Inc., makes **NO GUARANTEE** in reference to any specific class legality of any component. **ALL PRODUCTS ARE INTENDED FOR RACING AND OFF-ROAD USE AND MAY NOT BE LEGALLY USED ON THE HIGHWAY**. The products offered for sale are true race-car components and, in all cases, require some fabrication skill. **NO PRODUCT OR SERVICE IS DESIGNED OR INTENDED TO PREVENT INJURY OR DEATH**.

Chris Alston's Chassisworks 8661 Younger Creek Drive Sacramento, CA 95828 Phone: 916-388-0288 Technical Support: sales@cachassisworks.com

